

# Docker Connection & Health Check Guide

The current version is #ident

"@(#)\$Format:LocalFoodAI\_lanfr144:docker\_connection.md:Francois

Lange:lanfr144@school.lu:2026/06/11 08:26:59:Francois

Lange:lanfr144@school.lu:2026/06/11

08:26:59:1701828b122e0c319e59134ca6511a42ecad9297:: \$"

This document explains how to interact with the various Docker containers that power the Local Food AI system.

## Starting the Stack

To start the application and all its microservices:

```
# Standard environment
docker-compose up -d

# Windows / WSL environment (if applicable)
docker-compose -f docker-compose-wsl.yml up -d
```

## Connecting to Specific Containers

### 1. MySQL Database

To access the MySQL shell directly:

```
docker exec -it food-mysql-1 mysql -u root -p
```

\*Note: The password is defined in your `.env` file (MYSQL_ROOT_PASSWORD).*`

### 2. Ollama (AI Engine)

To manage LLM models or test the AI engine:

```
docker exec -it food-ollama-1 bash
# Inside the container, you can run:
# ollama list
# ollama run qwen2.5:1.5b
```

### 3. SearXNG (Web Search)

To view the SearXNG logs if the web search context is failing:

```
docker logs -f food-searxng-1
```

---

## 4. Zabbix (Telemetry)

If you need to access the Zabbix server or agent:

```
docker exec -it food-zabbix-server-1 bash
```

## Health Checks

You can verify that all application components are working using:

```
docker ps
```

Look for `Up (healthy)` in the STATUS column for the `mysql` service, and ensure `food-app-1` (Streamlit) is running without restarting.